

Intimidator Scan 305 IRC

HIGHLIGHTS

- Compact LED scanner with a 60 W light source shines through any environment
- Split the beam and cover larger areas with the crisp, 3-facet prism
- Convenient, wireless non-DMX control using the optional IRC-6 remote
- Link up to 4 fixtures to create eye-catching synchronized shows in Automated, Sound or Master/Slave modes
- Minimize programming time using built-in movement macros and move-in-black features
- Achieve flicker-free video operation with high-frequency LED dimming
- Save time running cables and extension cords by power linking multiple units
- Fits best in the CHS-40 VIP Gear Bag



SPEZIFIKATIONEN

- DMX Channels : 7 or 11
- DMX Connectors : 3-pin XLR
- Pan and Tilt : 180°/90°
- Colors : 8 + white, split colors, continuous scroll at variable speeds
- Gobos : 7 + open (5 metal + 2 glass), rotating, interchangeable, slot-n-lock, continuous scroll at variable speeds
- Light Source : 1 (white) 60 W (2.3 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 35 Hz
- PWM Frequency : 1,200 Hz
- Beam Angle : 15°
- Illuminance : 9,110 lux @ 2 m
- Power Linking : 5 units @ 120 V; 10 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 104 W, 1.5 A @ 120 V, 60 Hz
102 W, 0.8 A @ 230 V, 50 Hz
- Gobo Size : 23.9mm outside, 20.5 mm image, 1 mm max thickness
- Weight : 10 lb (4.6 kg)
- Size : 16.9 x 10 x 5.7 in (430 x 255 x 147 mm)
- Approvals : CE
- Optional Controllers : IRC-6
- Prism : 3-facet round, static

IM LIEFERUMFANG ENTHALTEN

- Power cord
- Hanging bracket with mounting hardware
- Warranty card
- Quick Reference Guide