

Intimidator Spot 355 IRC

HIGHLIGHTS

- Feature-packed moving head spot fitted with a 90 W LED to enhance any event or application
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Set, save, and recall 1 scene manually, directly from the full-color LCD display
- Link up to 4 fixtures to create eye-catching, synchronized shows in Automated or Sound mode
- Convenient, wireless non-DMX control using the optional IRC-6 remote
- Split the beam and cover a larger area with the rotating 3-facet prism
- Project crisp gobos from nearly any distance with the motorized focus
- Quickly and easily change gobos using the easy-access gobo door
- Throw light farther by decreasing the beam angle 5° using the manual zoom
- Save time running cables and extension cords by power linking multiple units
- Generate a synchronized show in Master/Slave mode with easy-to-access, built-in automated programs



SPEZIFIKATIONEN

- DMX Channels : 8 or 14
- DMX Connectors : 3-pin XLR
- Pan and Tilt : 540°/240°
- Pan and Tilt Ranges : 540°, 360°, 180° pan/240°, 180°, 90° tilt
- Colors : 8 + white, split colors, continuous scroll at variable speeds
- Gobos : 7 + open (5 metal + 2 glass), rotating, interchangeable, indexing, continuous scroll at variable speeds
- Light Source : 1 LED (white) 90 W (24.2 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 15.2 Hz
- PWM Frequency : 1.20 kHz
- Illuminance : (12°): 21,810 lux @ 2 m
(17°): 9,400 lux @ 2 m
(12°) 5,490 lux @ 5 m (17°) 2,626 lux @ 5 m
- Power Linking : 4 units @ 120 V; 7 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current : 186 W, 1.7 A @ 120 V, 60 Hz
179 W, 1 A @ 230 V, 50 Hz
- Gobo Size : 24 mm outside, 20 mm image, 1.1 mm max thickness
- Zoom Angle : (manual): 12° to 17°
- Weight : 24.6 lb (11.2 kg)
- Size : 10.6 x 13.4 x 15.4 in (268 x 340 x 392 mm)
- Approvals : CE
- Prism : 3-facet round, bidirectional rotation at variable speeds

IM LIEFERUMFANG ENTHALTEN

- Power cord
- Hanging bracket with mounting hardware
- Warranty card
- Quick Reference Guide