SlimPAR T12 ILS

HIGHLIGHTS

- Low-profile, high-output tri-color (RGB) LED Par
- ILS compatibility for use in the ILS ecosystem
- D-Fi USB compatibility for wireless Master/Slave or DMX control
- Convenient access to RGB color mixing and static colors with or without DMX
- Flicker-free operation suitable for on-camera use
- Save time running cables and extension cords by power linking multiple units
- Access built-in automated programs via IRC-6 remote, Master/Slave or DMX
- Fits best in the CHS-30 VIP Gear Bag
- Compact design easily fits inside sticks of TRUSST®

SPEZIFIKATIONEN

- DMX Channels : 3 or 8
- DMX Connectors : 3-pin XLR
- Light Source : 12 LEDs (tri-color RGB) 4.9 W (1.19A , 50,000 hours life expectancy
- Strobe Rate : 0 to 11 Hz
- Beam Angle : 17°
- Field Angle : 29°
- Illuminance : 3,362 lux @ 2 m
- Lumens : 1,415
- Power Linking : 13 units @ 120 V; 23 units @ 230 V
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current :
  43 W, 0.6 A @ 120 V, 60 Hz
  43 W, 0.3 A @ 230 V, 50 Hz
- Weight : 1.6 kg
- Size : 224.5 x 225.5 x 246 mm
- Bracket Mounting Hole : 13 mm
- Optional controllers : IRC=6

IM LIEFERUMFANG ENTHALTEN

- SlimPAR T12 ILS
- Stromkabel
- Quick Reference Guide